

F-370A

Mono Filament
Strapping Tape

DESCRIPTION

Mono filament strapping tape with a polyester (PET) film backing reinforced by continuous unidirectional glass fiber filaments, for industrial bundling, pallet stabilization and carton reinforcement where high longitudinal tensile strength and low elongation are required.

APPLICATIONS

Carton reinforcement and sealing, pallet stabilization, pipe and tube bundling, and steel bundling and securing.

STORAGE AND SHELF LIFE

Shelf life: 12 months from date of manufacture. Store in the original packaging in a cool, dry place away from direct sunlight and moisture.

Address:

No. 1156 Gaoqiao Avenue, Tongxiang Industrial Park, Zhejiang Province, China

Website: rivertape.com

E-mail: info@rivertape.com

River Tape Co., Ltd.

TECHNICAL DATA SHEET

Note: Typical values from our laboratory testing ;not to be considered specifications. Values measured with the standard synthetic rubber adhesive. Final performance should be validated under the actual substrate, load condition, application pressure and transport environment.

Property	Unit	F-370A-11/F-370A-14 /F-370A-15
Backing Material	—	Polyester (PET) film
Reinforcement	—	Continuous Glass Fiber Filaments
Adhesive Type	—	Synthetic Rubber (Hot-melt available)
Color	—	Clear / Transparent
Total Thickness	mm(mil)	0.11 (4.3) /0.14 (5.5)/0.15 (5.9)
Elongation at Break	%	6
Adhesion to Steel	N/25 mm (oz/in)	25(91)
Tensile Strength	N/25 mm (lb/in)	450(103)/600(137)/900(206)
Service temperature	°C(°F)	-10 to 70 (14 to 158)
Standard Roll Length	m(yd)	50 (55) and 55 (60)

